



## 300 Watt Series

*High Voltage Power You Can Depend On!*

- Up to 100kV Output
- 115 or 220 VAC Input Standard (Available in 85-265 VAC, Power Factor Corrected)
- Rugged and Designed to Last
- Standard 5 ¼” 19” Rack Mount {5.25” H x 19” L}
- Front Panel Digital LED Meters & Controls
- Available in Standard Ripple and Ultra Low Ripple
- OEM and Custom Designs available
- Remote Monitoring and Programming Standard HVC Pin-out. ( Analog Configurable & RS-232 available )
- Automatic Voltage, Current Crossover ( Power Regulation available )
- Self Protection from Arc, Voltage, Current , and Temperature

### Standard Power Supplies

Model	Max Power	Voltage	Current	Input VAC
HVCS-1-300	300 watts	1kV	300mA	115 to 220
HVCS-2-150	300 watts	2kV	150mA	115 to 220
HVCS-3-100	300 watts	3kV	100mA	115 to 220
HVCS-5-60	300 watts	5kV	60mA	115 to 220
HVCS-10-30	300 watts	10kV	30mA	115 to 220
HVCS-15-20	300 watts	15kV	20mA	115 to 220
HVCS-20-15	300 watts	20kV	15mA	115 to 220
HVCS-30-10	300 watts	30kV	10mA	115 to 220
HVCS-50-6	300 watts	50kV	6mA	115 to 220
HVCS-70-4	300 watts	70kV	4mA	115 to 220
HVCS-100-3	300 watts	100kV	3mA	115 to 220

Note: Specify {P or N} for Polarity at the end of the Model Number

High Voltage Concepts, LLC  
 577 North Main Street. Brewster, NY 10509  
 Phone: 845-278-8180 Fax: 845-278-8187  
[www.hvconcepts.com](http://www.hvconcepts.com)



## 300 Watt Series

*High Voltage Power You Can Depend On!*

### Ultra Low Ripple Power Supplies

Model	Max Power	Voltage	Current	Input VAC
HVCLR-1-300	300 watts	1kV	300mA	115 to 220
HVCLR-2-150	300 watts	2kV	150mA	115 to 220
HVCLR-3-100	300 watts	3kV	100mA	115 to 220
HVCLR-5-60	300 watts	5kV	60mA	115 to 220
HVCLR-10-30	300 watts	10kV	30mA	115 to 220
HVCLR-15-20	300 watts	15kV	20mA	115 to 220
HVCLR-20-15	300 watts	20kV	15mA	115 to 220

Note: Specify {P or N} for Polarity at the end of the Model Number

#### Specifications:

Line Regulation:  $\pm 0.001\%$  of Full Voltage

Load Regulation:  $\pm 0.005\%$  of Full Voltage

Ripple: Standard: 0.04% rms

Ultra Low Ripple: 200mVpp

Operating Temperature:  $-15^{\circ}\text{C}$  to  $50^{\circ}\text{C}$     Storage:  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$

Stability:  $\pm 0.01\%$  per hour

Note: Specifications are subject to change without notice

High Voltage Concepts, LLC  
577 North Main Street. Brewster, NY 10509  
Phone: 845-278-8180 Fax: 845-278-8187  
[www.hvconcepts.com](http://www.hvconcepts.com)